



GAS ENGINE ROLL CAGE SERIES



PRESSURE WASHERS / SINCE 1970

FEATURES

2.7 - 4.0 GPM @ 2400 to 3500 PSI
12V DC Burners



HOT WATER

OIL FIRED

BELT/DIRECT DRIVE

Heavy-duty regulator rectifier eliminates the need for battery

Stainless-steel coil skin provides extra durability and resists corrosion

Oil-fired Wayne burner

Lifting eyes let power equipment do the hoisting

6-gallon, removable, rust-proof polyethylene fuel tank has fuel gauge in cap

Protective Heavy-duty roll-cage chassis

Control box with adjustable temperature control, hour meter and burner on/off switch

Upstream detergent injection

Model 965SS:
Oil Fired, 3.0 GPM
@ 3000 PSI

Hotsy-designed triplex direct-drive pump carries a 7-year warranty

12" heavy-duty flat free tires

50-ft wire-braided high pressure hose with swivel on one end

Trigger gun control with cool-grip



Model 1075BE Compact:
4.0 GPM@ 3500 PSI;
Vanguard 400 engine; 12V
DC water heater (12V battery
required, not supplied)



California Air Resources Board Verified

MODEL	PART NO.	GPM	PSI	ENGINE	CARB COMP.	CCS	BURNER	BTU/HR	PUMP MODEL	DIMENSIONS (LXWXH)	SHIP WT (LBS)
871SS*	1.110-014.0	2.7	2400	Honda GX200	YES	196	12V DC	248,500	HP3035G	43"x27"x39"	410
965SS*	1.110-015.0	3.0	3000	Honda GX270	NO *	270	12V DC	248,500	HP3035G	47"x31"x41"	445
965SS CAL*	1.110-090.0	3.0	3000	Vanguard 400	YES	408	12V DC	248,500	HP3035G	47"x31"x41"	445
1065SS*	1.110-010.0	3.5	3000	Honda GX340	NO *	337	12V DC	309,900	HS3540G.3	47"x31"x45"	495
1065SSE†	1.110-011.0	3.5	3000	Honda GX340	NO *	337	12V DC	309,900	HS3540G.3	47"x31"x45"	510
1065SSE CAL†	1.110-089.0	3.5	3000	Vanguard 400	YES	408	12V DC	309,900	HS3540G.3	47"x31"x45"	510
1075SSE†	1.110-012.0	4.0	3500	Honda GX390	NO *	389	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075SSE CAL†	1.110-080.0	4.0	3500	Vanguard 400	YES	408	12V DC	309,900	HS4040G.3	47"x31"x45"	520
1075BE Compact†	1.110-088.0	4.0	3500	Vanguard 400	YES	408	12V DC	309,900	HM4035	47"x31"x45"	520
1075BE Compact†	1.110-099.0	4.0	3500	Honda GX390	NO *	389	12V DC	309,900	HM4035	47"x31"x45"	520

* CARB Compliance required for sale in California. * Battery not required † 12V battery required, but not supplied E = Electric-start engine B= Belt

NEW BELT DRIVE MODELS
1075BE - COMPACT!

HOTSY.COM

IT'S WHAT THE PROS USE

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We meet the CETA testing specs for machine performance at +.10% and in some cases are tighter within +. 5% of listed specifications.

Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified.

© 2023 Kärcher North America
P/N HOT_GasEngineRollCage Effective 01/23

Distributed by:



1210 N Oregon Ave, Pasco, WA 99301
northstarhotsy.com | info@northstarhotsy.com
(509) 547-2323