



# MODEL 555HE Hot-Water Pressure Washer

North America's #1 Brand of High-Pressure Cleaning Equipment

Electric / Direct Drive



**High-efficiency burner** delivers higher cleaning performance and lower operating costs

**Stainless-steel coil skin** provides extra durability to withstand the elements

**Simple, easy-to-use control panel** includes adjustable temperature control, hour meter, heavy-duty heater and pump motor switches

**Built-in wand and hose holder** provides convenient storage

**Convenient hose-reel bracket** accepts swivel or stationary reels for ease in hose maneuverability and storage (extra bracket needed for stationary reels)

**Heavy-duty trigger gun and 36" wand** with insulated cool grips

**4-pole, low RPM, 2 HP, 115V, 1PH electric motor (TEFC)** comes with thermal overload protection

**50-ft. high-pressure hose** for easy maneuverability around a large cleaning area

**Upstream detergent injection** ensures high-pressure sudsing for better cleaning

**Pressure relief valve** protects the machine and user from thermal expansion

**36-ft. power cord** with safety **Ground Fault Circuit Interrupter (GFCI breaker)**

**3 nozzles** with quick coupling



**Large 12" flat free tires**

**Rust-proof 8-gallon diesel tank** with fuel gauge

## FEATURES

- 2.2 GPM @ 1300 PSI
- Direct-Drive Triplex Pump
- 7-Year Pump Warranty
- ETL-Certified to UL-1776 safety standards



**Hotsy triplex, direct-drive, positive-displacement pump** carries a 7-year warranty on the crankcase



**Heating coils** carry a 5-year warranty

[www.Hotsy.com](http://www.Hotsy.com)

**Nothing Cleans Like a Hotsy!**

# 555HE Hot Water **ELECTRIC** Model

■ Diesel-Fired Heater ■ 2.2 GPM @ 1300 PSI ■ Hotsy Triplex Pump with 7-year warranty ■ Portability standard ■ ETL-Certified for safety

## Designed for tough, industrial cleaning.

### SPECIFICATIONS

### DIRECT DRIVE

MODEL	GPM	PSI	HP	VOLT/PH	AMP	FUEL	BTU/HR	PUMP	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
<b>555HE</b>	2.2	1300	2	115/1	20	Oil	185,000	Triplex HFP2230SR	Direct	Std	50'	385

Machine dimensions: 42" x 29" x 42" (LxWxH)

Shipping dimensions: 41" x 36" x 50" (LxWxH)

### DON'T FORGET THE SOAP!

Hotsy pressure washers clean best when matched with specially formulated Hotsy detergents. Nearly all contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and to fight corrosion in your equipment. All are highly concentrated, so a little goes a long way.



**HOTSY SOLUTION SELECTOR**  
What's the best detergent for your next job? Find out with our solution selector. Scan this QR code or visit [HOTSY.com](http://HOTSY.com)

### SERVICE & REPAIR

Hotsy has more than 175 local dealers in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Hotsy has factory-trained service technicians who will provide on-site maintenance for your cleaning equipment. Our techs have most common replacement parts on their service truck, and will quickly have your washer running smoothly.



FIND OUT MORE ONLINE: [HOTSY.COM](http://HOTSY.COM)

### OPTIONS FOR MODEL 555HE

- Auto Start/Stop
- Float Tank
- 100' Hose Reel
- 100' 360° Pivot Hose Reel



### PARTS & ACCESSORIES

Your local Hotsy dealer would be happy to provide an onsite demonstration to determine which pressure washer accessories will help speed cleaning and lower your costs. Hotsy dealers stock thousands of pressure washer replacement parts such as high pressure hose, trigger guns, high pressure nozzles, pumps, engines, motors, unloaders, filters and wands. In addition, you'll find a number of accessories designed to speed cleaning, the most common accessories are telescoping wands, pivot and non-pivot hose reels, flat surface cleaners and high pressure turbo nozzles.



Distributed by:



**Nothing Cleans Like a Hotsy!**

Tel: (800) 525-1976 Fax: (888) 880-9631  
[www.Hotsy.com](http://www.Hotsy.com) email: [info@Hotsy.com](mailto:info@Hotsy.com)  
HOT\_555HE Effective 10/19



Specifications & product descriptions subject to change without notice. Hotsy's manufacturing facilities have established and apply a quality and environmental management system to be ISO 9001:2008 and ISO 14001:2001 certified. © Kärcher North America

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We exceed CETA testing specs for machine performance within a tolerance of +/-5% of listed specifications.